

Electrical Specification

- Power Supply: (1) AC 110V/220V, 60 Hz
- (2) Rechargeable Battery 18V 3.4A
- (3) External Battery DC 18V 4A
- Frequency Response: 70 - 15,000 Hz
- Input Circuit (wired mic): 1/2 600Ω
- Record Output: 0 dBV 1k Ω
- Speakers: 4 Ohms, 8"
- Audio Output: 40W RMS
- Input Jacks: 3
- Output Jacks: 1
- Dimensions: 266 mm (W) x 423 mm (H) x 242 mm (D)
- Net Weight: : 9.2 Kgs (included rechargeable battery)

Wireless Microphone

- Frequency: 160~270Mhz
- Mic: 1. Condenser Lapel mic
2. Dynamic Handheld mic
- Transmission power: 35mW
- Spurious Harmonic : -50dB
- Current Consumption: <10mA
- Battery Voltage :DC 9V(006P)



Receiver Specification

- Frequency Range: 160 ~ 270Mhz
- Receiving Sensitivity: more than 80dB(at 20dBμV input)
- Signal to Noise Ratio: more than 95dB(at 60dB μg input)
- Receiving System: Superheterodyne System
- Intermediate Frequency: 10.7MHz

CD Player

- Use Friendly
- LCD Display with backlight
- Control function:
 - A-B repeat
 - Random
 - 1/All Repeat
 - Program
 - Forward
 - Rewind
 - Play
 - Stop / Reject



- Use friendly
- LCD Display with backlight
- Auto Stop Mechanism
- One touch Recording
- Feeding direction : horizontal
- Tracking System : 4 Track
- Operation function:
 - Reset / Mode
 - Reject
 - Record
 - Fast forward / Forward
 - Stop Rewind / Fast Rewind



Includes rechargeable batteries...

